

Hybrid 5M/4M H.265+ DVR

4/8/16CH H.265+ Hybrid 5-in-1 DVR DVR-JH4511/DVR-JH8521/DVR-JH6521



DVR-JH4511





DVR-JH8521/DVR-JH6521



- AHD/TVI/CVI/CVBS/IP record.
- H.265 high profile (H.265+) compression algorithm, low bit rate, high picture quality.
- Dual stream - individual network video streaming and DVR record streaming.
- Phone remote view (iPhone / iPad / Android).
- Smart channel settings: Live / playback screen digital zoom, playback camera title and date / time position movable.
- Operation log list / Network online users list check.
- Intensive security function by chosen AUTHORITY.
- Convenient backup by AVI file.
- HDD data retention days / Daylight saving time / NTP.

Model		DVR-JH4511	DVR-JH8521	DVR-JH6521
Input	AHD/TVI/CVI (Max.)	4CH	8CH	16CH
	IPC Connection Channel	6CH (1~6 selectable)	16CH (1~16 selectable)	16CH (1~16 selectable)
Simultaneously Local Playback (Max.)		4CH	8CH	16CH
Output	VGA	1920x1080 / 1280x1024		
	HDMI	3840x2160 / 1920x1080 / 1280x1024 / 1024x768		
	CVBS	1 (Simultaneously or SPOT)		
Display Channel		1 / 4 / 9	1 / 4 / 9 / 16	1 / 4 / 9 / 16 / 25
Total Recording Resolution (HD Analog)	5MP	48	96	192
	5MPL	80	160	320
	4MP	48(PAL) / 60(NTSC)	96(PAL) / 120(NTSC)	192(PAL) / 240(NTSC)
	4MPL	100(PAL) / 120(NTSC)	200(PAL) / 240(NTSC)	400(PAL) / 480(NTSC)
	1080P	100(PAL) / 120(NTSC)	200(PAL) / 240(NTSC)	400(PAL) / 480(NTSC)
IP Recording	Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P		
	Recording Rate	Max 25(PAL) / 30(NTSC) per channel		
Record Quality		Highest / Higher / Medium / Lower / Lowest		
Compression Method		H.265 High Profile (H.265+)		
Recording Mode		Auto / manual / schedule / motion / alarm		
Multi-task		Live / Record / Play / Network / Backup		
Motion Detect		22 x18 grids camera for all channel		
E-SATA		1		
Backup		USB 2.0 / Network remote backup		
Storage		SATA x1 (10TB)	SATA x2 (each 10TB)	
Audio Input / Audio Output		RCA x4 input / RCA x1 output	RCA x8 input / RCA x1 output	
Alarm Input / Audio Output		Input x4 ; Output x1	Input x8 ; Output x2	Input x16 ; Output x4
HDD Record Mode		Full stop / Overwrite		
PTZ Control		PELCO-P, PELCO-D, CoC(UTC)		
Mobile Surveillance		iPhone / iPad / Android		
Ethernet		10/100 M Base-T	10/100/1000 M Base-T	
Network-Function		Support licensed CMS / APP / IE		
Network Connection		TCP/IP, PPPoE, DHCP, DDNS(Auto DDNS)		
Client Application		Display / Playback / Backup / DVR control / PTZ Control		
Power Source		DC12V		
Operating Temperature		5°C~40°C (41°F~104°F)		
Operating Humidity		Less than 90%		
Dimension		300(W) x 52.1(H) x 248.4(D)mm	380(W) x 52.1(H) x 268.4(D)mm	

Dimension Unit : mm



DVR-JH4511



DVR-JH8521/DVR-JH6521