

# IP CAMERA

## IPC-4D71SM

- H.265 / H.264
- 4MP ( 2560 × 1440 )
- 20 ~ 30 M IR night view distance
- 3 DNR,WDR
- ICR auto switch, true day / night
- Support ROI coding
- Support smart phone, iPad, remote monitoring
- IP67 ingress protection
- PoE power supply

**RoHS** CE FC


# 4MP IP IR WATER-PROOF DOME CAMERA



## IPC-4D71SM

Camera	
Image Sensor	1 / 2.7 " CMOS
Image Size	2560 × 1440
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.04 lux @ F2.26, AGC ON; 0 lux with IR
Lens	Board 2.8 mm @F2.0 / 3.6 mm @F2.2
Horizontal view Angle	110° / 89°
IR Distance	20 ~ 30 m
WDR	Digital WDR
Day & Night	ICR auto switch
BLC	YES
HLC	YES
Defog	YES
Digital NVR	3 DNR
Image	
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile
Resolution	4MP (2560 × 1440) , 3MP (2304 × 1296), 1080P(1920 × 1080) , 720P (1280 × 720) , D1 , CIF , 480 × 240
Main Stream (S1)	4MP/ 3MP/ 1080P @ 30fps
Sub Stream (S2)	720P / D1 / CIF @ 30fps
Third Stream (S3)	D1 / CIF / 480×240 @30fps
Bit Rate	64 Kbps ~ 5 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, ...etc. adjustable through client software or web browser
ROI	Support ROI coding, each ROI to be configured separately
Audio	
Audio Compression	G711A / U
Two-way audio	-
Interfaces	
Network	RJ45
Video Output	-
Audio line in	Built-in MIC × 1
Audio line out	-
Alarm Input	-
Alarm Output	-
Storage	
SD card	-
Network remote storage	Yes
Hardware Reset	-

Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 4 users Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Smart Alarm	Motion detection
Intelligent Analytics	Exception, Line Crossing, Intrusion (optional)
General function	Watermark, IP address filtering, video mask, heartbeat, password protection
PoE	Yes
Others	
Power Supply	DC12V / PoE
Power Consumption	<5.5 W
Operating Environment	- 30 °C ~ 60 °C (-22° F ~ 140° F) Humidity: less than 95 % (non-condensing)
Dimensions	Φ 94.6 × 82.8 mm
Weight	Approx. 450g
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)
Ingress Protection	IP67

Accessories			
			
B627	B639	B609	
			
B615	B616	B642	B628