

IP CAMERA

IPC-4T57SM

- H.265 / H.264
- 4MP (2560 × 1440)
- 20 ~ 30 M IR night view distance
- 3 DNR,WDR
- ICR auto switch, true day / night
- Support ROI coding
- Support smart phone, iPad, remote monitoring
- IP67 ingress protection
- PoE power supply







RoHS CE FC

4MP IP IR WATER-PROOF BULLET CAMERA



IPC-4T57SM

Camera	
Image Sensor	1 / 2.7 " CMOS
Image Size	2560 × 1440
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.04 lux @F2.26, AGC ON; 0 lux with IR
Lens	Board 2.8 mm @F2.0 / 3.6 mm @F2.2
Horizontal view Angle	110° / 89°
IR Distance	20~30 m
WDR	Digital WDR
Day & Night	ICR auto switch
BLC	YES
HLC	YES
Defog	YES
Digital DNR	3 DNR
Image	
Video Compression	H.265 / H.264
H.264 Compression Standard	Main Profile
Resolution	4MP (2560 × 1440) , 3MP (2304 × 1296), 1080P(1920 × 1080) , 720P (1280 × 720), D1 , CIF , 480 × 240
Main Stream (S1)	4MP/ 3MP/ 1080P @30fps
Sub Stream (S2)	720P / D1 / CIF @30fps
Third Stream (S3)	D1 / CIF / 480×240 @30fps
Bit Rate	64 Kbps ~ 5 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen,NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Audio	
Audio Compression	-
Two-way audio	-
Interfaces	
Network	RJ45
Video Output	-
Audio line in	-
Audio line out	-
Alarm Input	-
Alarm Output	-
Storage	
SD card	-
Network remote storage	Yes
Hardware Reset	-

Functions		
Remote Monitoring	Web browsing,CMS remote control	
Online Connection	Support simultaneous monitoring for up to 4 users Support multi-stream real time transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS	
Interface Protocol	ONVIF	
Smart Alarm	Motion detection	
Intelligent Analytics	Exception,Line Crossing,Intrusion(optional)	
General function	Watermark, video mask, heartbeat, password protection	
PoE	Yes	
Others		
Power Supply	DC12V / PoE	
Power Consumption	< 5W	
Operating Environment	- 30 ° C ~ 60 ° C (-22° F~140° F) Humidity: less than 95 % (non-condensing)	
Dimensions	74.5 × 74.5 × 167.5 mm	
Weight	Approx. 380g	
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)	
Ingress Protection	IP67	
Accessories		
		
B627	B640	B639
		
B615	B616	B628