

SSV-XHD-80F-5M

4.5" 5M FULL HD 4 in 1 PTZ CAMERA WITH IR

- * Keep original analog system
- * Real time transmission, lossless video
- 5M / 10X Zoom**
- * Long distance transmission up to 500 meters
- * OSD menu available / IR distance 120M
- * 4.5" Total Metal body construction, IP66 rate protection
- * IR illumination & power consumption is variable dependant on zoom factor
- * AHD/TVI/CVI/CVBS selectable
- * Coax function is available



Specification

Camera

Sensor	NVP2477+05A10
Total pixels	5.0MP
Privacy mask	Support
Lens	10X f=5.1mm~51mm
FOV	H: 54.8° (W) ~3.4° (T) V: 41° (W) ~2.5° (T)
Iris	F1.6~F2.7
Min. illumination	Color: 0.1Lux \ B/W: 0.01Lux
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
D/N	IR-CUT
D-WDR	Support
S/N Ratio	≥50dB

Dome

Horizontal Rotation Range	360°
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Horizontal Rotation Speed	0.02 ~200°/s
Tilt Rotation Speed	0.02 ~100°/s
Ratio Speed	Support
Preset Points	220
Go to Preset Speed	200°/s
360° Scan	1-64 grades setting available
A-B Scan	User programmable
A-B Scan Speed	1-64 grades setting available
Park Time	1-60mins setting available
Dwell Preset	1-60s interval available
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
PWR on Action	Memory/Tour 1/360 scan/AB scan/Preset 1-8/None
Operation menu	English
Pan and Tilt position display	Support

Communication Protocol	Pelco-D, Pelco-P
Baud Rate	1200/2400/4800/9600bps (Default is 2400bps)
Video interface output	AHD/TVI/CVI/CVBS selectable
Communication mode	RS485 (+-)/coaxial cable
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Power	DC12V 3A
Lightning Protection	Transient voltage 6000V
Auto Control IR LED	PWM
LEDs	Array 42Mil
IR distance	Up to 120 meters
Support ambient light detection	IR illumination on 1-9 grades selectable;